



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 400 nm-700 nm
3. DIAMETER TOLERANCE: +0.0/-0.1mm
4. THICKNESS TOLERANCE: ±0.1mm
5. FOCAL LENGTH: -30.0 mm±1%
6. BACK FOCAL LENGTH(REF): -32.2 mm
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE POWER(S2): $3\lambda/2$ @ 632.8nm
10. SURFACE IRREGULARITY(S2): $\lambda/4$ @ 632.8nm
11. SURFACE FLATNESS: $\lambda/2$ @632.8 nm
12. CENTRATION: <3arcmin
13. CHAMFER: <0.2 mm, 45°
14. COATING(S1,S2): AR COATING Ravg <0.5% @ 400nm-700nm

DRAWING PROJECTION			 cruis-optics.com			
	NAME	DATE	PCB25430-A			
DRAWN	WENSHUO	2024/08/26	$\phi 25.4$ mm, f=-30.0 PLANO CONCAVE LENS AR COATING 400 nm-700 nm			
APPROVAL	SHAWN	2024/08/26	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7		2:1	A